

## **TYRES**

Product group	Tyres	
Item number	15235805	
Valid tyre size	24 R 20.5	
LI / SI / PR	176 F	
TL/TT	TL	
Brand	Alliance	
Tread pattern	390 Industrial HD	





## Notes and features

- The Alliance 390 HD is ideal for longer transport and grassland use.
- Its non-directional block tread pattern enables smooth driving during longer road journeys and protects the soil when driving on grassland.
- The low rolling resistance minimises fuel consumption.
- The high tread pattern depth ensures the tyre has a long service life.
- The HD version with 4 steel belts and specially reinforced bead enables higher loading capacities and better durability compared with the standard tyre.



## **Technical Informations**

Item number	15235805
EAN	7291050066662
Valid tyre size	24 R 20.5
LI / SI / PR	176 F
TL/TT	TL
Brand	Alliance
Tread pattern	390 Industrial HD
Carcass properties	All-Steel,HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	195,00
Recommended rim size	18.00
Maximum air pressure [bar].	6,00
Section width (mm)	605
Outer diameter of tyre [mm].	1372
Stat. radius (SLR) [mm]	620
Rolling circumference [mm].	4208
Tread depth (mm)	22,7
Number of lugs	64x2
Tyre capacity 75% [ltr.]	411.75
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 F	7100	80		6,00	