

## TYRES

|                 |              |
|-----------------|--------------|
| Product group   | Tyres        |
| Item number     | 15272113     |
| Valid tyre size | 10 - 16.5    |
| LI / SI / PR    | 129 A2, 8 PR |
| TL/TT           | TL           |
| Brand           | Alliance     |
| Tread pattern   | SK 903       |



## Notes and features

- The Alliance SK-903 was developed specifically for skid steer loaders.
- The open and deep shoulders provide good traction on loose off-road surfaces.
- The flatter radius and solid lugs in the centre of the tread improve the wear resistance of the tyre.
- The special rim protection on the side wall prevents impact injuries.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 15272113      |
| EAN                          | 8903635016229 |
| Valid tyre size              | 10 - 16.5     |
| LI / SI / PR                 | 129 A2, 8 PR  |
| TL/TT                        | TL            |
| Brand                        | Alliance      |
| Tread pattern                | SK 903        |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 19,96         |
| Recommended rim size         | 8.25          |
| Maximum air pressure [bar].  | 4,10          |
| Section width (mm)           | 260           |
| Outer diameter of tyre [mm]. | 773           |
| Stat. radius (SLR) [mm]      | 356           |
| Rolling circumference [mm].  | 2351          |
| Tread depth (mm)             | 14,2          |
| E-Ready                      | No            |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 129 A2 | 1850               | 10           |               | 4,10                     |              |