

TYRES

Product group	Tyres
Item number	15272114
Valid tyre size	10 - 16.5
LI / SI / PR	134 A2, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	SK 903



Notes and features

- The Alliance SK-903 was developed specifically for skid steer loaders.
- The open and deep shoulders provide good traction on loose off-road surfaces.
- The flatter radius and solid lugs in the centre of the tread improve the wear resistance of the tyre.
- The special rim protection on the side wall prevents impact injuries.

Technical Informations

Item number	15272114
EAN	8903635018841
Valid tyre size	10 - 16.5
LI / SI / PR	134 A2, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	SK 903
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	19,60
Recommended rim size	8.25
Maximum air pressure [bar].	5,20
Section width (mm)	260
Outer diameter of tyre [mm].	773
Stat. radius (SLR) [mm]	356
Rolling circumference [mm].	2351
Tread depth (mm)	14,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A2	2120	10		5,20	