

TYRES

Product group	Tyres
Item number	15272114
Valid tyre size	10 - 16.5
LI / SI / PR	134 A2, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	SK 903





Notes and features

- The Alliance SK-903 was developed specifically for skid steer loaders.
- The open and deep shoulders provide good traction on loose off-road surfaces.
- The flatter radius and solid lugs in the centre of the tread improve the wear resistance of the tyre.
- The special rim protection on the side wall prevents impact injuries.



Technical Informations

Item number	15272114
EAN	8903635018841
Valid tyre size	10 - 16.5
LI / SI / PR	134 A2, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	SK 903
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	19,60
Recommended rim size	8.25
Maximum air pressure [bar].	5,20
Section width (mm)	260
Outer diameter of tyre [mm].	773
Stat. radius (SLR) [mm]	356
Rolling circumference [mm].	2351
Tread depth (mm)	14,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A2	2120	10		5,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.