

TYRES

Product group	Tyres
Item number	15272125
Valid tyre size	12 - 16.5
LI / SI / PR	140 A2, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	SK 903



Notes and features

- The Alliance SK-903 was developed specifically for skid steer loaders.
- The open and deep shoulders provide good traction on loose off-road surfaces.
- The flatter radius and solid lugs in the centre of the tread improve the wear resistance of the tyre.
- The special rim protection on the side wall prevents impact injuries.

Technical Informations

Item number	15272125
EAN	8903635016236
Valid tyre size	12 - 16.5
LI / SI / PR	140 A2, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	SK 903
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	26,49
Recommended rim size	9.75
Maximum air pressure [bar].	4,50
Section width (mm)	307
Outer diameter of tyre [mm].	831
Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2510
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A2	2500	10		4,50	