Bohnenkamp Moving Professionals

19.09.2024

TYRES

Product group	Tyres	
Item number	15272280	
Valid tyre size	16.0 / 70 - 20	
LI / SI / PR	166 A2 / 149 B, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	326	





Notes and features

- Outstanding self-cleaning properties and optimum traction and flotation for all off-road applications.
- The ozone- & weather-resistant rubber compound guarantees a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15272280
EAN	8903635002536
Valid tyre size	16.0 / 70 - 20
Alternative size 1	405/70-20
LI / SI / PR	166 A2 / 149 B, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	326
TRA Code	E2/L2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	68,13
Recommended rim size	13SDC
Maximum air pressure [bar].	4,50
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3130
Tread depth (mm)	24,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A2	5300	10		4,50	
149 B	3250	50		3,50	

19.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.