

TYRES

Product group	Tyres
Item number	15272350
Valid tyre size	600 / 40 - 22.5
LI / SI / PR	175 A6 / 171 A8
TL/TT	TL
Brand	Alliance
Tread pattern	344



Notes and features

- Reinforced tyre bead for premium performance on difficult ground conditions.
- Closely-overlapping lugs in the centre of the tread pattern reduce the rolling resistance on hard surfaces.
- The narrow distance between lugs in the centre of the tyre reduces the rolling resistance on hard surfaces.
- Steel inserts enable safe use and allow even distribution of pressure.
- Suitable for excavators, dumpers and skid steer loaders.

Technical Informations

Item number	15272350
EAN	7291050064132
Valid tyre size	600 / 40 - 22.5
LI / SI / PR	175 A6 / 171 A8
TL/TT	TL
Brand	Alliance
Tread pattern	344
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	127,00
Recommended rim size	AG20.00
Maximum air pressure [bar].	7,00
Section width (mm)	590
Outer diameter of tyre [mm].	1090
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3358
Tread depth (mm)	43,5
Number of lugs	15x2
Tyre capacity 75% [ltr.]	177
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A6	6900	30		7,00	
171 A8	6150	40		7,00	