

TYRES

Product group	Tyres
Item number	15272530
Valid tyre size	15.5 - 25
LI / SI / PR	149 B, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308



Notes and features

- Designed for demanding use on front loaders.
- The nylon construction & specially angled and overlapping tread blocks ensure optimum traction on all surfaces, as well as good self-cleaning.
- Designed for use on wheel loaders & graders.

Technical Informations

Item number	15272530
EAN	8903635000259
Valid tyre size	15.5 - 25
LI / SI / PR	149 B, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	77,72
Recommended rim size	12
Permitted rim size	12SDC
Maximum air pressure [bar].	2,50
Section width (mm)	394
Outer diameter of tyre [mm].	1277
Stat. radius (SLR) [mm]	564
Rolling circumference [mm].	3720
Tread depth (mm)	24,1
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 B	3250	50		2,50	