

TYRES

Product group	Tyres
Item number	15272540
Valid tyre size	17.5 - 25
LI / SI / PR	153 B, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308



Notes and features

- Designed for demanding use on front loaders.
- The nylon construction & specially angled and overlapping tread blocks ensure optimum traction on all surfaces, as well as good self-cleaning.
- Designed for use on wheel loaders & graders.

Technical Informations

Item number	15272540
EAN	8903635000266
Valid tyre size	17.5 - 25
LI / SI / PR	153 B, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	96,36
Recommended rim size	14
Permitted rim size	14SDC
Maximum air pressure [bar].	2,25
Section width (mm)	445
Outer diameter of tyre [mm].	1348
Stat. radius (SLR) [mm]	606
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4147
Tread depth (mm)	25,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 B	3650	50		2,20	