

TYRES

Product group	Tyres
Item number	15272542
Valid tyre size	17.5 - 25
LI / SI / PR	158 B, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308





Notes and features

- Designed for demanding use on front loaders.
- The nylon construction & specially angled and overlapping tread blocks ensure optimum traction on all surfaces, as well as good self-cleaning.
- Designed for use on wheel loaders & graders.



Technical Informations

Item number	15272542
EAN	8903635000273
Valid tyre size	17.5 - 25
LI / SI / PR	158 B, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	103,78
Recommended rim size	14
Permitted rim size	14SDC
Maximum air pressure [bar].	3,00
Section width (mm)	444
Outer diameter of tyre [mm].	1348
Stat. radius (SLR) [mm]	599
Rolling circumference [mm].	3940
Tread depth (mm)	25,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 B	4250	50		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.