

TYRES

Product group	Tyres
Item number	15272543
Valid tyre size	17.5 - 25
LI / SI / PR	158 B, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	318





Notes and features

- Non-directional tyre with a special rubber compound against punctures & abrasion.
- Sturdy tyre for use on dumpers, wheel loaders and graders.



Technical Informations

Item number	15272543
EAN	8903635000310
Valid tyre size	17.5 - 25
LI / SI / PR	158 B, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	318
TRA Code	E3/L3/G3
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	111,24
Recommended rim size	14
Permitted rim size	14SDC
Maximum air pressure [bar].	3,00
Section width (mm)	444
Outer diameter of tyre [mm].	1348
Stat. radius (SLR) [mm]	599
Rolling circumference [mm].	3940
Tread depth (mm)	31,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 B	4250	50		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.