

TYRES

Product group	Tyres
Item number	15272560
Valid tyre size	20.5 - 25
LI / SI / PR	167 B, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308



Notes and features

- Designed for demanding use on front loaders.
- The nylon construction & specially angled and overlapping tread blocks ensure optimum traction on all surfaces, as well as good self-cleaning.
- Designed for use on wheel loaders & graders.

Technical Informations

Item number	15272560
EAN	8903635000280
Valid tyre size	20.5 - 25
LI / SI / PR	167 B, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	308
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	154,26
Recommended rim size	17
Maximum air pressure [bar].	3,50
Section width (mm)	520
Outer diameter of tyre [mm].	1492
Stat. radius (SLR) [mm]	658
Rolling circumference [mm].	4340
Tread depth (mm)	28,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 B	5450	50		2,75	
	8250	10		3,50	