

TYRES

Product group	Tyres
Item number	15272567
Valid tyre size	20.5 - 25
LI/SI/PR	16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	307





Notes and features

- The Alliance 307 is a versatile tyre for use in difficult conditions.
- The tyre provides optimum traction on uneven surfaces and is particularly suitable for all types of dump truck, wheel loader and grader applications.
- The arrangement of the lugs, which interlock in the centre of the tread, enables very good self-cleaning, low rolling resistance and excellent stability.
- The strong casing, reinforced sidewalls and cut-resistant compound ensure a long service life.



Technical Informations

Item number	15272567
EAN	8903635017820
Valid tyre size	20.5 - 25
LI / SI / PR	16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	307
TRA Code	L2/E2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	130,80
Recommended rim size	17.00/2.5
Maximum air pressure [bar].	2,25
Section width (mm)	518
Outer diameter of tyre [mm].	1493
Stat. radius (SLR) [mm]	674
Rolling circumference [mm].	4445
Tread depth (mm)	28,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	4000	40		2,25	
	8250	10		3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.