

## **TYRES**

Product group	Tyres
Item number	15272572
Valid tyre size	20.5 - 25
LI / SI / PR	170 B, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	318





## Notes and features

- Non-directional tyre with a special rubber compound against punctures & abrasion.
- Sturdy tyre for use on dumpers, wheel loaders and graders.



## **Technical Informations**

Item number	15272572
EAN	8903635000334
Valid tyre size	20.5 - 25
LI / SI / PR	170 B, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	318
TRA Code	E3/L3/G3
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	168,70
Recommended rim size	17
Maximum air pressure [bar].	3,25
Section width (mm)	520
Outer diameter of tyre [mm].	1492
Stat. radius (SLR) [mm]	658
Rolling circumference [mm].	4340
Tread depth (mm)	28,0
Tyre capacity 75% [ltr.]	540
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 B	6000	50		3,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.