# Bohnenkamp Moving Professionals

### **TYRES**

Product group	Tyres	
Item number	15272581	
Valid tyre size	23.5 - 25	
LI / SI / PR	191 A2 / 177 B, 20 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	318	



#### Notes and features

- Non-directional tyre with a special rubber compound • against punctures & abrasion.
- Sturdy tyre for use on dumpers, wheel loaders and • graders.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15272581
EAN	8903635000341
Valid tyre size	23.5 - 25
LI / SI / PR	191 A2 / 177 B, 20 PR
TL/TT	ть
Brand	Alliance
Tread pattern	318
TRA Code	E3/L3/G3
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	232,21
Recommended rim size	19.5
Maximum air pressure [bar].	3,00
Section width (mm)	597
Outer diameter of tyre [mm].	1617
Stat. radius (SLR) [mm]	716
Rolling circumference [mm].	4720
Tread depth (mm)	31,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
191 A2	10900	10		3,00	
177 B	7300	50		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.