

TYRES

Product group	Tyres
Item number	15283112
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Dual Master 506



Notes and features

- The Dual Master 506 was developed for dual excavator tyre configurations.
- Its special sidewall construction enables close contact between the tyres and prevents stones from penetrating between them.
- This dispenses with the need for special spacer rings.
- Its strong all-steel radial casing provides stability, protection against damage, a long service life, lower fuel consumption and ride comfort.
- The 506 tread pattern is characterised by effective off-road and particularly on-road performance.
- The shoulder lugs enable good grip on softer surfaces, more rubber around the tyre centre ensures smooth and stable handling on harder surfaces.
- Special retreadable EM casing.

Technical Informations

Item number	15283112
EAN	8903635020936
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Dual Master 506
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	87,00
Recommended rim size	9
Maximum air pressure [bar].	9,00
Section width (mm)	330
Outer diameter of tyre [mm].	1100
Stat. radius (SLR) [mm]	509
Rolling circumference [mm].	3366
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		9,00	