

TYRES

Product group	Tyres
Item number	15283115
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Dual Master 528



Notes and features

- The Alliance Dual Master 528 has been specifically designed for twin excavator tyres.
- The special sidewall construction allows close contact between the tyres and thus prevents stones from penetrating between them.
- This means that no spacer ring is needed between the tyres.
- The strong all-steel radial carcass provides good stability, protection against damages, a long service life, low fuel consumption and good ride comfort.
- The angled lugs enable a good grip on soft surfaces.
- More rubber around the centre of the tyre provides a smooth and stable ride on hard surfaces.
- Special retreadable EM carcass.

Technical Informations

Item number	15283115
EAN	7291050061148
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Dual Master 528
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	85,39
Recommended rim size	9
Permitted rim size	8.25
Maximum air pressure [bar].	8,50
Section width (mm)	326
Outer diameter of tyre [mm].	1100
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3090
Tread depth (mm)	25,0
Tyre capacity 75% [ltr.]	105
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40		8,50	