

## TYRES

Product group	Tyres
Item number	15283117
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Dual Master 528



## Notes and features

- The Alliance Dual Master 528 has been specifically designed for twin excavator tyres.
- The special sidewall construction allows close contact between the tyres and thus prevents stones from penetrating between them.
- This means that no spacer ring is needed between the tyres.
- The strong all-steel radial carcass provides good stability, protection against damages, a long service life, low fuel consumption and good ride comfort.
- The angled lugs enable a good grip on soft surfaces.
- More rubber around the centre of the tyre provides a smooth and stable ride on hard surfaces.
- Special retreadable EM carcass.

## Technical Informations

Item number	15283117
EAN	8903635020967
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Dual Master 528
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	87,00
Recommended rim size	9
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	326
Outer diameter of tyre [mm].	1100
Stat. radius (SLR) [mm]	508
Rolling circumference [mm].	3343
Tread depth (mm)	25,0
Number of lugs	30x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		9,00	