

TYRES

Product group	Tyres	
Item number	15284003	
Valid tyre size	250 / 75 R 16	
LI / SI / PR	120 G	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multiuse 550	





Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.



Technical Informations

Item number	15284003
EAN	7291050065801
Valid tyre size	250 / 75 R 16
LI / SI / PR	120 G
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	20,60
Recommended rim size	8
Maximum air pressure [bar].	4,50
Section width (mm)	253
Outer diameter of tyre [mm].	781
Stat. radius (SLR) [mm]	361.5
Rolling circumference [mm].	2341
Tread depth (mm)	15,5
Number of lugs	42x2
Tyre capacity 75% [ltr.]	50
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Inde	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120	1400	90		4,50	