

TYRES

Product group	Tyres
Item number	15284005
Valid tyre size	250 / 80 R 16
LI / SI / PR	126 A8 / 123 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

Technical Informations

Item number	15284005
EAN	7291050063128
Valid tyre size	250 / 80 R 16
LI / SI / PR	126 A8 / 123 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,31
Recommended rim size	8
Permitted rim size	7, 9
Maximum air pressure [bar].	4,40
Section width (mm)	267
Outer diameter of tyre [mm].	815
Stat. radius (SLR) [mm]	368
Rolling circumference [mm].	2470
Tread depth (mm)	17,5
Tyre capacity 75% [ltr.]	54
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
126 A8	1700	40		4,40	
123 D	1550	65		4,40	