

TYRES

Product group	Tyres
Item number	15284051
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

Technical Informations

Item number	15284051
EAN	7291050060387
Valid tyre size	500 / 70 R 24
Alternative size 1	19.5LR24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	117,04
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	4,00
Section width (mm)	505
Outer diameter of tyre [mm].	1308
Stat. radius (SLR) [mm]	591
Rolling circumference [mm].	3920
Tread depth (mm)	28,8
Tyre capacity 75% [ltr.]	278
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	