# Bohnenkamp Moving Professionals

20.09.2024

### TYRES

Product group	Tyres
Item number	15284069
Valid tyre size	400 / 80 R 24
LI / SI / PR	149 A8 / 144 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550





#### Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15284069
EAN	8903635020233
Valid tyre size	400 / 80 R 24
Alternative size 1	14.9R24
LI / SI / PR	149 A8 / 144 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	86,10
Recommended rim size	DW13
Maximum air pressure [bar].	3,20
Section width (mm)	404
Outer diameter of tyre [mm].	1249
Stat. radius (SLR) [mm]	566
Rolling circumference [mm].	3730
Tread depth (mm)	27,0
Number of lugs	42x2
Tyre capacity 75% [ltr.]	195.6
Guarantee period	5 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		3,20	
144 D	2800	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.