

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15284090 |
| Valid tyre size | 480 / 65 R 28 |
| LI / SI / PR | 154 A8 / 149 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Multiuse 550 |



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15284090 |
| EAN | 7291050057202 |
| Valid tyre size | 480 / 65 R 28 |
| LI / SI / PR | 154 A8 / 149 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Multiuse 550 |
| M+S | M+S |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 114,79 |
| Recommended rim size | 15 |
| Permitted rim size | 14, 16 |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 475 |
| Outer diameter of tyre [mm]. | 1339 |
| Stat. radius (SLR) [mm] | 607 |
| Rolling circumference [mm]. | 4020 |
| Tread depth (mm) | 26,0 |
| Tyre capacity 75% [ltr.] | 249 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 154 A8 | 3750 | 40 | | 3,20 | |
| 149 D | 3250 | 65 | | 3,20 | |