

TYRES

Product group	Tyres
Item number	15284100
Valid tyre size	540 / 65 R 30
LI / SI / PR	161 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550



Bohnenkamp
Moving Professionals



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

Technical Informations

Item number	15284100
EAN	7291050050326
Valid tyre size	540 / 65 R 30
LI / SI / PR	161 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	135,13
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	3,20
Section width (mm)	545
Outer diameter of tyre [mm].	1461
Stat. radius (SLR) [mm]	666
Rolling circumference [mm].	4402
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	347
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		3,20	
156 D	4000	65		3,20	