

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15284102       |
| Valid tyre size | 600 / 70 R 30  |
| LI / SI / PR    | 161 A8 / 158 D |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | Multiuse 550   |



## Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 15284102       |
| EAN                          | 7291050063098  |
| Valid tyre size              | 600 / 70 R 30  |
| LI / SI / PR                 | 161 A8 / 158 D |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | Multiuse 550   |
| M+S                          | M+S            |
| Carcass properties           | Steel Belted   |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 196,65         |
| Recommended rim size         | 20             |
| Permitted rim size           | 18             |
| Maximum air pressure [bar].  | 2,40           |
| Section width (mm)           | 611            |
| Outer diameter of tyre [mm]. | 1602           |
| Stat. radius (SLR) [mm]      | 727            |
| Rolling circumference [mm].  | 4792           |
| Tread depth (mm)             | 30,0           |
| Tyre capacity 75% [ltr.]     | 540            |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 161 A8 | 4625               | 40           |               | 2,40                     |              |
| 158 D  | 4250               | 65           |               | 2,40                     |              |