

TYRES

Product group	Tyres
Item number	15284111
Valid tyre size	480 / 80 R 34
LI / SI / PR	164 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550





Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.



Technical Informations

Item number	15284111
EAN	8903635019824
Valid tyre size	480 / 80 R 34
Alternative size 1	18.4R34
LI / SI / PR	164 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	153,80
Recommended rim size	DW15L
Maximum air pressure [bar].	3,20
Section width (mm)	479
Outer diameter of tyre [mm].	1632
Stat. radius (SLR) [mm]	739
Rolling circumference [mm].	4912
Tread depth (mm)	27,0
Number of lugs	48x2
Tyre capacity 75% [ltr.]	380.4
Guarantee period	5 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		3,20	
159 D	4375	65		3,20	