

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 15284195       |
| Valid tyre size | 710 / 70 R 42  |
| LI / SI / PR    | 181 A8 / 177 D |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | Multiuse 550   |





## Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.



## **Technical Informations**

| Item number                  | 15284195       |
|------------------------------|----------------|
| EAN                          | 7291050062343  |
| Valid tyre size              | 710 / 70 R 42  |
| LI / SI / PR                 | 181 A8 / 177 D |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | Multiuse 550   |
| M+S                          | M+S            |
| Carcass properties           | Steel Belted   |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 308,78         |
| Recommended rim size         | 23             |
| Maximum air pressure [bar].  | 2,80           |
| Section width (mm)           | 716            |
| Outer diameter of tyre [mm]. | 2053           |
| Stat. radius (SLR) [mm]      | 939            |
| Rolling circumference [mm].  | 6187           |
| Tread depth (mm)             | 36,0           |
| Number of lugs               | 48x2           |
| Tyre capacity 75% [ltr.]     | 960            |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 181 A8 | 8250               | 40           |               | 2,80                        |              |
| 177 D  | 7300               | 65           |               | 2,80                        |              |