

## **TYRES**

Product group	Tyres
Item number	15284205
Valid tyre size	620 / 80 R 42
LI / SI / PR	181 A8 / 177 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550





## Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.



## **Technical Informations**

Item number	15284205
EAN	7291050062350
Valid tyre size	620 / 80 R 42
LI / SI / PR	181 A8 / 177 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	273,63
Recommended rim size	20
Maximum air pressure [bar].	3,20
Section width (mm)	625
Outer diameter of tyre [mm].	2055
Stat. radius (SLR) [mm]	948
Rolling circumference [mm].	6201
Tread depth (mm)	36,1
Number of lugs	48x2
Tyre capacity 75% [ltr.]	817.5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		3,20	
177 D	7300	65		3,20	