

TYRES

Product group	Tyres	
Item number	15284300	
Valid tyre size	400 / 80 R 28	
LI / SI / PR	151 A8 / 146 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multiuse Professional 551	





Notes and features

- The Alliance Multiuse Professional 551 is a new and recently developed tyre for use on municipal tractors, backhoe loaders and other agro-industrial machinery.
- Its additional sipes on the tread blocks ensure optimum handling, ride comfort and traction on dry, wet and snowcovered surfaces.
- The tyre is marked M+S and specially equipped for winter use
- Due to the unique combination of special rubber compound and tread pattern design, the tyre guarantees excellent performance and a long service life.
- The strong steel-belted casing provides damage protection and optimum stability.



Technical Informations

Item number	15284300
EAN	7291050083065
Valid tyre size	400 / 80 R 28
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse Professional 551
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,50
Recommended rim size	DW13
Permitted rim size	DW14L
Maximum air pressure [bar].	3,20
Section width (mm)	404
Outer diameter of tyre [mm].	1352
Stat. radius (SLR) [mm]	616
Rolling circumference [mm].	4039
Tread depth (mm)	25,0
Number of lugs	42x2
Tyre capacity 75% [ltr.]	226.5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,20	
146 D	3000	65		3,20	