

TYRES

Product group	Tyres
Item number	15284305
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 151 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse Professional 551



Notes and features

- The Alliance Multiuse Professional 551 is a new and recently developed tyre for use on municipal tractors, backhoe loaders and other agro-industrial machinery.
- Its additional sipes on the tread blocks ensure optimum handling, ride comfort and traction on dry, wet and snow-covered surfaces.
- The tyre is marked M+S and specially equipped for winter use.
- Due to the unique combination of special rubber compound and tread pattern design, the tyre guarantees excellent performance and a long service life.
- The strong steel-belted casing provides damage protection and optimum stability.

Technical Informations

Item number	15284305
EAN	7291050083119
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 151 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse Professional 551
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	108,00
Recommended rim size	DW14L
Permitted rim size	DW15L, DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	440
Outer diameter of tyre [mm].	1418
Stat. radius (SLR) [mm]	646
Rolling circumference [mm].	4260
Tread depth (mm)	26,0
Number of lugs	42x2
Tyre capacity 75% [litr.]	282.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		3,20	
151 D	3450	65		3,20	