

TYRES

Product group	Tyres
Item number	15284870
Valid tyre size	335 / 80 R 18
LI / SI / PR	136 A8
TL/TT	TL
Brand	Alliance
Tread pattern	608



Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- High lugs in the shoulder area for traction on loose surfaces.
- Optimised rolling resistance allows fuel savings.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.

Technical Informations

Item number	15284870
EAN	8903635011606
Valid tyre size	335 / 80 R 18
Alternative size 1	12.5R18
LI / SI / PR	136 A8
TL/TT	TL
Brand	Alliance
Tread pattern	608
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	49,25
Recommended rim size	11
Permitted rim size	10
Maximum air pressure [bar].	3,20
Section width (mm)	343
Outer diameter of tyre [mm].	992
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	2985
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A8	2240	40		3,20	