

TYRES

Product group	Tyres
Item number	15284900
Valid tyre size	405 / 70 R 18
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Alliance
Tread pattern	608



Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.
- High lugs in the shoulder area for traction on loose surfaces.
- Optimised rolling resistance allows fuel savings.

Technical Informations

Item number	15284900
EAN	7291050060905
Valid tyre size	405 / 70 R 18
Alternative size 1	16.0/70R18
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Alliance
Tread pattern	608
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,51
Recommended rim size	W13
Maximum air pressure [bar].	3,75
Section width (mm)	408
Outer diameter of tyre [mm].	1025
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	3084
Tread depth (mm)	18,5
Tyre capacity 75% [ltr.]	141
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10		3,75	
141 B	2575	50		3,75	