

TYRES

Product group	Tyres
Item number	15284907
Valid tyre size	335 / 80 R 20
LI / SI / PR	147 A2 / 136 B
TL/TT	TL
Brand	Alliance
Tread pattern	608



Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.
- High lugs in the shoulder area for traction on loose surfaces.
- Optimised rolling resistance allows fuel savings.

Technical Informations

Item number	15284907
EAN	7291050062220
Valid tyre size	335 / 80 R 20
Alternative size 1	12.5R20
LI / SI / PR	147 A2 / 136 B
TL/TT	TL
Brand	Alliance
Tread pattern	608
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	49,49
Recommended rim size	11
Permitted rim size	W10, W11, 11SDC, 12, 12SDC
Maximum air pressure [bar].	3,75
Section width (mm)	350
Outer diameter of tyre [mm].	1044
Stat. radius (SLR) [mm]	465
Rolling circumference [mm].	3148
Tread depth (mm)	18,5
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A2	3075	10		3,75	
136 B	2240	50		3,75	