

TYRES

Product group	Tyres
Item number	15284911
Valid tyre size	365 / 80 R 20
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Alliance
Tread pattern	608



Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.
- High lugs in the shoulder area for traction on loose surfaces.
- Optimised rolling resistance allows fuel savings.

Technical Informations

Item number	15284911
EAN	8903635023272
Valid tyre size	365 / 80 R 20
Alternative size 1	14.5R20
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Alliance
Tread pattern	608
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,60
Recommended rim size	W11
Maximum air pressure [bar].	3,70
Section width (mm)	360
Outer diameter of tyre [mm].	1092
Stat. radius (SLR) [mm]	478
Rolling circumference [mm].	3326
Tread depth (mm)	18,5
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10		3,70	
141 B	2575	50		3,70	