

TYRES

Product group	Tyres
Item number	15284921
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 143 B
TL/TT	TL
Brand	Alliance
Tread pattern	608



Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- High lugs in the shoulder area for traction on loose surfaces.
- Optimised rolling resistance allows fuel savings.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.

Technical Informations

Item number	15284921
EAN	8903635022398
Valid tyre size	405 / 70 R 20
Alternative size 1	16/70R20
LI / SI / PR	155 A2 / 143 B
TL/TT	TL
Brand	Alliance
Tread pattern	608
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,60
Recommended rim size	W13
Permitted rim size	13-20SDC, 14
Maximum air pressure [bar].	3,72
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	491
Rolling circumference [mm].	3265
Tread depth (mm)	18,5
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A2	3875	10		3,70	
143 B	2725	50		3,72	