

TYRES

Product group	Tyres	
Item number	15285030	
Valid tyre size	365 / 70 R 18	
LI / SI / PR	146 A2 / 135 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	606	





Notes and features

- For light earthmoving work.
- Non-directional tread pattern.

• High operating hours and best traction.



Technical Informations

Item number	15285030
EAN	7291050023733
Valid tyre size	365 / 70 R 18
LI / SI / PR	146 A2 / 135 B
TL/TT	TL
Brand	Alliance
Tread pattern	606
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	58,74
Recommended rim size	11
Permitted rim size	13
Maximum air pressure [bar].	3,75
Section width (mm)	400
Outer diameter of tyre [mm].	1000
Stat. radius (SLR) [mm]	440
Rolling circumference [mm].	2902
Tread depth (mm)	22,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A2	3000	10		3,75	
135 B	2180	50		3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.