

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15285200 |
| Valid tyre size | 405 / 70 R 24 |
| LI / SI / PR | 158 A2 |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 606 |



Notes and features

- For light earthmoving work.
- Non-directional tread pattern.
- High operating hours and best traction.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15285200 |
| EAN | 7291050024075 |
| Valid tyre size | 405 / 70 R 24 |
| LI / SI / PR | 158 A2 |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 606 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 84,45 |
| Recommended rim size | 13 |
| Permitted rim size | 13SDC |
| Maximum air pressure [bar]. | 3,75 |
| Section width (mm) | 425 |
| Outer diameter of tyre [mm]. | 1180 |
| Stat. radius (SLR) [mm] | 538 |
| Rolling circumference [mm]. | 3548 |
| Tread depth (mm) | 22,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 158 A2 | 4250 | 10 | | 3,75 | |