

TYRES

Product group	Tyres	
Item number	15285200	
Valid tyre size	405 / 70 R 24	
LI / SI / PR	158 A2	
TL/TT	TL	
Brand	Alliance	
Tread pattern	606	





Notes and features

- For light earthmoving work.
- Non-directional tread pattern.

• High operating hours and best traction.



Technical Informations

Item number	15285200
EAN	7291050024075
Valid tyre size	405 / 70 R 24
LI / SI / PR	158 A2
TL/TT	TL
Brand	Alliance
Tread pattern	606
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	84,45
Recommended rim size	13
Permitted rim size	13SDC
Maximum air pressure [bar].	3,75
Section width (mm)	425
Outer diameter of tyre [mm].	1180
Stat. radius (SLR) [mm]	538
Rolling circumference [mm].	3548
Tread depth (mm)	22,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A2	4250	10		3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.