Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15285250	
Valid tyre size	280 / 80 R 18	
LI / SI / PR	132 A8 / 132 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Industrial 580	



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15285250
EAN	7291050056649
Valid tyre size	280 / 80 R 18
Alternative size 1	10.5R18
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	38,76
Recommended rim size	8
Permitted rim size	9, 10
Maximum air pressure [bar].	4,00
Section width (mm)	282
Outer diameter of tyre [mm].	905
Stat. radius (SLR) [mm]	418
Rolling circumference [mm].	2776
Tread depth (mm)	29,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40		4,00	
132 B	2000	50		4,00	

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.