

## **TYRES**

Product group	Tyres	
Item number	15285253	
Valid tyre size	300 / 75 R 18	
LI / SI / PR	142 A8 / 142 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Industrial 580	





## Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.



## **Technical Informations**

Item number	15285253
EAN	8903635017707
Valid tyre size	300 / 75 R 18
Alternative size 1	12.0R18
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	39,60
Recommended rim size	9
Maximum air pressure [bar].	5,00
Section width (mm)	295
Outer diameter of tyre [mm].	908
Stat. radius (SLR) [mm]	420
Rolling circumference [mm].	2697
Tread depth (mm)	33,0
Number of lugs	17x2
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		5,00	
142 B	2650	50		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.