# Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15285260	
Valid tyre size	280 / 80 R 20	
LI / SI / PR	133 A8 / 133 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Industrial 580	



#### Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

# Bohnenkamp Moving Professionals

#### **Technical Informations**

Item number	15285260
EAN	7291050050234
Valid tyre size	280 / 80 R 20
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	48,07
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	4,00
Section width (mm)	282
Outer diameter of tyre [mm].	956
Stat. radius (SLR) [mm]	437
Rolling circumference [mm].	2846
Tread depth (mm)	28,0
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		4,00	
133 B	2060	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.