

TYRES

Product group	Tyres
Item number	15285271
Valid tyre size	340 / 80 R 20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Technical Informations

Item number	15285271
EAN	8903635020080
Valid tyre size	340 / 80 R 20
Alternative size 1	12.5R20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	59,60
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	4,00
Section width (mm)	343
Outer diameter of tyre [mm].	1052
Stat. radius (SLR) [mm]	477
Rolling circumference [mm].	3185
Tread depth (mm)	32,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,00	
144 B	2800	50		4,00	