

## **TYRES**

Product group	Tyres	
Item number	15285279	
Valid tyre size	400 / 70 R 18	
LI / SI / PR	147 A8 / 147 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Industrial 580	





## Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.



## **Technical Informations**

Item number	15285279
EAN	8903635022664
Valid tyre size	400 / 70 R 18
Alternative size 1	16.0/70R18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	67,00
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	4,00
Section width (mm)	404
Outer diameter of tyre [mm].	1017
Stat. radius (SLR) [mm]	461
Rolling circumference [mm].	3073
Tread depth (mm)	35,3
Number of lugs	17x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		4,00	
147 B	3075	50		4,00	