

TYRES

Product group	Tyres
Item number	15285279
Valid tyre size	400 / 70 R 18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Technical Informations

Item number	15285279
EAN	8903635022664
Valid tyre size	400 / 70 R 18
Alternative size 1	16.0/70R18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	67,00
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	4,00
Section width (mm)	404
Outer diameter of tyre [mm].	1017
Stat. radius (SLR) [mm]	461
Rolling circumference [mm].	3073
Tread depth (mm)	35,3
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		4,00	
147 B	3075	50		4,00	