

TYRES

Product group	Tyres	
Item number	15285281	
Valid tyre size	400 / 70 R 20	
LI / SI / PR	149 A8 / 149 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Industrial 580	



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.



Technical Informations

Item number	15285281
EAN	8903635020103
Valid tyre size	400 / 70 R 20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	76,18
Recommended rim size	13
Permitted rim size	12, 14
Maximum air pressure [bar].	4,00
Section width (mm)	410
Outer diameter of tyre [mm].	1072
Stat. radius (SLR) [mm]	485
Rolling circumference [mm].	3239
Tread depth (mm)	32,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	
149 B	3250	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.