

## TYRES

|                 |                     |
|-----------------|---------------------|
| Product group   | Tyres               |
| Item number     | 15285305            |
| Valid tyre size | 405 / 70 R 24       |
| LI / SI / PR    | 152 A8 / 152 B      |
| TL/TT           | TL                  |
| Brand           | Alliance            |
| Tread pattern   | Agro Industrial 580 |



## Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

## Technical Informations

|                              |                     |
|------------------------------|---------------------|
| Item number                  | 15285305            |
| EAN                          | 7291050060578       |
| Valid tyre size              | 405 / 70 R 24       |
| LI / SI / PR                 | 152 A8 / 152 B      |
| TL/TT                        | TL                  |
| Brand                        | Alliance            |
| Tread pattern                | Agro Industrial 580 |
| Carcass properties           | Steel Belted        |
| Antistatic                   | No                  |
| Tyre colour                  | Black               |
| ECE regulation number        | ECE 106             |
| Nettogewicht [kg] (gültig)   | 85,60               |
| Recommended rim size         | 13                  |
| Maximum air pressure [bar].  | 4,00                |
| Section width (mm)           | 404                 |
| Outer diameter of tyre [mm]. | 1170                |
| Stat. radius (SLR) [mm]      | 538                 |
| Rolling circumference [mm].  | 3521                |
| Tread depth (mm)             | 36,0                |
| E-Ready                      | No                  |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 152 A8 | 3550               | 40           |               | 4,00                     |              |
| 152 B  | 3550               | 50           |               | 4,00                     |              |