

## TYRES

Product group	Tyres
Item number	15285312
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580



## Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

## Technical Informations

Item number	15285312
EAN	8903635021964
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Carcass properties	C.R.,Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	107,80
Recommended rim size	DW15L
Permitted rim size	DW14L
Maximum air pressure [bar].	4,00
Section width (mm)	462
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	567
Rolling circumference [mm].	3701
Tread depth (mm)	39,5
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	