

TYRES

Product group	Tyres
Item number	15285335
Valid tyre size	480 / 80 R 26
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Technical Informations

Item number	15285335
EAN	7291050057387
Valid tyre size	480 / 80 R 26
Alternative size 1	18.4R26
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	130,15
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	3,20
Section width (mm)	489
Outer diameter of tyre [mm].	1423
Stat. radius (SLR) [mm]	642
Rolling circumference [mm].	4268
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	402
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		3,20	
160 B	4500	50		3,20	