

## **TYRES**

Product group	Tyres
Item number	15285340
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580





## Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.



## **Technical Informations**

Item number	15285340
EAN	7291050056670
Valid tyre size	440 / 80 R 28
Alternative size 1	16.9R28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	125,56
Recommended rim size	14
Permitted rim size	15
Maximum air pressure [bar].	3,20
Section width (mm)	460
Outer diameter of tyre [mm].	1410
Stat. radius (SLR) [mm]	642
Rolling circumference [mm].	4183
Tread depth (mm)	40,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		3,20	
156 B	4000	50		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.