

TYRES

Product group	Tyres
Item number	15285350
Valid tyre size	500 / 70 R 28
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Technical Informations

Item number	15285350
EAN	8903635010784
Valid tyre size	500 / 70 R 28
Alternative size 1	19.5LR28
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	135,70
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	4,00
Section width (mm)	503
Outer diameter of tyre [mm].	1411
Stat. radius (SLR) [mm]	643
Rolling circumference [mm].	4187
Tread depth (mm)	30,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	